

**Bath/Rainshower System**  
**7765-BD-80P1**


**INTRODUCTION:**

The simple tube-form design, brings out the modern beauty of linear shape. This series combines the refined surface, multiple functions, and humanization operating design as a perfect elegant demonstration of modern bath equipment. In the meanwhile, it inherits the durability and the convenient from the previous product generation, making a comfortable bathing space for customers.



**DESCRIPTION:**

- 1.Brass of casting body meets ISO CuZn40Pb standard.
- 2.Finish meets the standard of ASTM-SC2.
- 3.The faucet should be used at the water pressure from 1.5 to 4.5 kg/cm<sup>2</sup>.
- 4.Adjust the water supply to hand shower or rain shower by pressing diverter.
- 5.Ceramic valve with CERAMTEC ceramic disc/(Germany).
- 6.Elastic shower hose can be extended from 1.5 meter to 2 meter.
- 7.Adjustable angle of the hand-shower bracket.
- 8.The available distance between two centers of wall water-outlet is 122mm to 178mm.
- 9.The swiveling shower arm could be adjusted for the different spray position within available range.
- 10.Coordinates with other products in Pan I collection.



unit:mm

**Certification:**

**Fixing Kits:**

- 1.SUS 304 Stainless Steel Screws\*2.
- Hex Key 1/8"\*1.  
Set Screw\*2.  
Plastic Anchors\*2.

**AWARD:**